

7/25/2025 9:29 AM ALEXANDRA COLEMAN alexandracoleman@engineeringexpress.com documents\projects\23-69317 2023 fbc update structall insulated patio cover over open wall\work\drawings & cad\23-69317c - structall mps open room systems.dwg



# INSULATED ROOF PATIO COVER WITH OPEN WALLS





PERFORMANCE EVALUATION  
FREESTANDING OR HOST ATTACHED, UP TO 12' & 15' SPAN

THIS IS A NON-SITE-SPECIFIC PERFORMANCE EVALUATION. A DESIGN PROFESSIONAL SHALL BE RESPONSIBLE FOR CERTIFYING THE APPLICATION OF THIS INFORMATION TO ANY SITE-SPECIFIC LOCATION

NOTE: THIS DOCUMENT IS NOT TO BE USED WITHOUT AN ORIGINAL PEN SIGNATURE & RAISED SEAL OR ELECTRONICALLY VERIFIABLE ELECTRONIC SIGNATURE MEETING ALL DISCLAIMERS SET FORTH HEREIN. RUBBED PENCIL COPIES ARE NOT PERMITTED FOR USE IN ANY WAY

COPIES WITHOUT  
ORIGINAL PE SEAL NOT  
VALID FOR PERMIT

SPACE RESERVED FOR  
CERTIFYING ENGINEER'S  
DIGITAL OR PHYSICAL SEAL  
& DATE OF CERTIFICATION



## DESIGN NOTES:

1. POSITIVE AND NEGATIVE DESIGN PRESSURES CALCULATED FOR USE WITH THIS SYSTEM SHALL BE DETERMINED BY OTHERS ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH THE STRUCTURAL REQUIREMENTS OF THE FLORIDA BUILDING CODE 8TH (2023) EDITION, 2012/2015/2018/2021 IBC/IRC, AS WELL AS CURRENT VERSIONS OF THE MN, NC, NJ, NY, OH, SC, & VA BUILDING CODES AS APPLICABLE. CODE ENFORCED COMPLIES WITH STATE OF SEAL AND IF MULTIPLE VERSIONS LISTED THEN MOST STRINGENT APPLIES.
2. DESIGN SHALL UTILIZE ASD DESIGN METHOD USING ASCE 7-22 OR ASCE 7-16 BASED ON APPLICABLE CODE.
3. CONTRACTOR SHALL INVESTIGATE AND CONFORM TO ALL LOCAL BUILDING CODE AMENDMENTS WHICH MAY APPLY. DESIGN CRITERIA OR SPANS BEYOND STATED HEREIN MAY REQUIRE ADDITIONAL SITE SPECIFIC SEALED ENGINEERING.
4. SEISMIC DESIGN SHALL BE CONSIDERED WHEN REVIEWING FOR EACH USE USING LOAD TABLE LIMITATIONS PROVIDED.
5. THE EXISTING HOST STRUCTURE MUST BE CAPABLE OF SUPPORTING THE LOADED ENCLOSURE AS DETERMINED BY OTHERS OR BY SPECIAL ENGINEERING. NO WARRANTY IS CONTAINED HEREIN.
6. THIS STRUCTURE SHALL REMAIN OPEN (NO SCREENS OR WALLS) WITHOUT ADDITIONAL ENGINEERING.

## GENERAL NOTES:

1. STRUCTURE SHALL BE FABRICATED IN ACCORDANCE WITH ALL GOVERNING CODES. CONTRACTOR SHALL INVESTIGATE AND CONFORM TO ALL LOCAL BUILDING CODE AMENDMENTS WHICH MAY APPLY.
2. THE ARCHITECT/ENGINEER OF RECORD FOR THE PROJECT SUPERSTRUCTURE WITH WHICH THIS DESIGN IS USED SHALL BE RESPONSIBLE FOR THE INTEGRITY OF ALL SUPPORTING SURFACES TO THIS DESIGN WHICH SHALL BE COORDINATED BY THE PERMITTING CONTRACTOR.

## MATERIAL:

3. ALUMINUM MEMBERS ANCHORS SHALL BE SPACED WITH 2xDIAMETER END DISTANCE AND 2.5xDIAMETER MIN. SPACING TO ADJACENT ANCHORS, UNLESS NOTED OTHERWISE.
4. ALL CONCRETE ANCHORS SHALL BE INSTALLED TO NON-CRACKED CONCRETE ONLY.
5. THE CONTRACTOR IS RESPONSIBLE TO INSULATE ALL MEMBERS FROM DISSIMILAR MATERIALS TO PREVENT ELECTROLYSIS.
6. ALL ALUMINUM SHALL BE 6063-T6 ALLOY AND TEMPER UNLESS NOTED OTHERWISE.
7. ALL CONCRETE TO REACH A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI IN 7 DAYS.

## CONNECTIONS:

7. ALL FASTENERS TO BE #12 OR GREATER SAE GRADE 5 UNLESS NOTED OTHERWISE. FASTENERS SHALL BE CADMIUM-PLATED OR OTHERWISE CORROSION-RESISTANT MATERIAL AND SHALL COMPLY WITH "SPECIFICATIONS FOR ALUMINUM STRUCTURES" SECTION J.3.7.2 BY THE ALUMINUM ASSOCIATION, INC., & ANY APPLICABLE FEDERAL, STATE, AND/OR LOCAL CODES.
8. ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS' RECOMMENDATIONS. MINIMUM EMBEDMENT SHALL BE AS NOTED HEREIN. MINIMUM EMBEDMENT AND EDGE DISTANCE EXCLUDES STUCCO, FOAM, BRICK, AND OTHER WALL FINISHES.

## OTHER:

9. ENGINEER SEAL AFFIXED HERETO VALIDATES STRUCTURAL DESIGN AS SHOWN ONLY. USE OF THIS SPECIFICATION BY CONTRACTOR, et. al. INDEMNIFIES & SAVES HARMLESS THIS ENGINEER FOR ALL COST & DAMAGES INCLUDING LEGAL FEES & APPELLATE FEES RESULTING FROM MATERIAL FABRICATION, SYSTEM ERECTION, & CONSTRUCTION PRACTICES BEYOND THAT WHICH IS CALLED FOR BY LOCAL, STATE, & FEDERAL CODES & FROM DEVIATIONS OF THIS PLAN.
10. THE PRODUCT DETAILED HEREIN IS GENERIC AND DOES NOT PROVIDE INFORMATION FOR A SPECIFIC SITE. FOR SITE CONDITIONS DIFFERENT FROM THE CONDITIONS DETAILED HEREIN, A LICENSED PROFESSIONAL SHALL PREPARE SITE EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED.
11. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE THIS CERTIFICATION.
12. EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED

**DIGITAL SEAL NOTICE:**  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [ECALC.IO/DS](https://ecalculator.io) FOR MORE INFORMATION.  
**PRINTED DOCUMENT NOTICE:**  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE. **VALID FOR 1 PERMIT ONLY U.S.A.**

**ENGINEERING  
EXPRESS®**

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
[ENGINEERINGEXPRESS.COM](https://ENGINEERINGEXPRESS.COM)

STRUCTALL BUILDING SYSTEMS, INC.

350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627

INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FBC 2023 (23-69317)	CLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

23-69317

SCALE: NTS UNLESS NOTED

1 OF 1





VISIT [ECALC.IO/STRUCTALL](https://ecalculator.io/structall)

FOR ENGINEER CERTIFIED ORIGINALS  
& MORE INFORMATION ABOUT THIS DOCUMENT  
OR SCAN THIS QR CODE

VISIT [ENGINEERINGEXPRESS.COM/STORE](https://ENGINEERINGEXPRESS.COM/STORE)  
FOR ADDITIONAL PLANS, REPORTS & RESOURCES



7/25/2025 9:29 AM ALEXANDRA COLEMAN alexandracoleman@engineeringexpress.com projects\23-69317 2023 fbc update structural insulated patio cover over open wall\work\drawings & cad\23-69317c - structural mps open room systems.dwg



NOTE: KNEEBRACES SHALL BE PROVIDED IN BOTH DIRECTIONS AT ALL SUPPORTING POSTS

NOTE: MITRE KNEEBRACES TO FIT AROUND PURLINS AT RAFTER CONNECTION POINTS AS NEEDED. MAINTAIN ANCHORAGE INTEGRITY.

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

**DIGITAL SEAL NOTICE:**  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [E.C.A.L.C.I.O/D5](http://E.C.A.L.C.I.O/D5) FOR MORE INFORMATION.  
**PRINTED DOCUMENT NOTICE:**  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
**VALID FOR 1 PERMIT ONLY U.N.O.**

**ENGINEERING EXPRESS®**

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
[ENGINEERINGEXPRESS.COM](http://ENGINEERINGEXPRESS.COM)

STRUCTALL BUILDING SYSTEMS, INC.

350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627

INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FBC 2023 (23-69317)	CLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

23-69317

SCALE: NTS UNLESS NOTED

2


EXTRUSIONS- COMPONENTS

#12 SAE GRADE 5  
STITCH SCREWS AT  
12" MAX O.C., TYP.


SELF MATING BEAM  
SCHEDULE:

BEAM TYPE	B	H	tb	th
2"x4" SMB	2"	4"	0.056"	0.046"
2"x5" SMB	2"	5"	0.058"	0.050"
2"x6" SMB	2"	6"	0.060"	0.065"
2"x7" SMB	2"	7"	0.060"	0.057"
2"x8" SMB	2"	8"	0.105"	0.075"
2"x9" SMB	2"	9"	0.112"	0.072"
2"x10" SMB	2"	10"	0.187"	0.092"


A 2"x4" - 2"x10" SELF  
MATING BEAMS




B 6.7 C-BEAM



C1a 2"x7" EDGE BEAM



C1b 2"x7" EDGE BEAM  
REINFORCEMENT



C2 2"x5" - 2"x10"  
EDGE BEAMS

EDGE BEAM  
SCHEDULE:


BEAM TYPE	B	H	th
2"x5" EDGE	2"	5"	0.088"
2"x8" EDGE	2"	8"	0.125"
2"x10" EDGE	2"	10"	0.125"

COPIES WITHOUT  
ORIGINAL PE SEAL NOT  
VALID FOR PERMIT


SPACE RESERVED FOR  
CERTIFYING ENGINEER'S  
DIGITAL OR PHYSICAL SEAL  
& DATE OF CERTIFICATION

**DIGITAL SEAL NOTICE:**  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS  
ITEM HAS BEEN DIGITALLY SIGNED BY THE  
ABOVE-SIGNING ENGINEER ON THE DATE  
ADJACENT TO THE SEAL. PRINTED COPIES OF THIS  
DOCUMENT ARE NOT CONSIDERED SIGNED AND  
SEALED AND THE SIGNATURE MUST BE VERIFIED  
ON ANY ELECTRONIC COPIES.  
VISIT [E.C.A.L.C./IO/DS](http://E.C.A.L.C./IO/DS) FOR MORE INFORMATION.  
**PRINTED DOCUMENT NOTICE:**  
IF THIS DOCUMENT IS PRINTED & DOES NOT  
CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE &  
SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR  
USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
**VALID FOR 1 PERMIT ONLY U.N.O.**

**ENGINEERING  
EXPRESS®**  
POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
[ENGINEERINGEXPRESS.COM](http://ENGINEERINGEXPRESS.COM)




D 2"x4" TILT BEAM  
2.5 DEGREE TILT SLOPE  
NOMINAL HEIGHT DIFFERENTIAL (0.1"+-)




E 3" - 6" SQUARE POST

SQUARE POST  
SCHEDULE:

BEAM TYPE	B	tb
3"x3"x0.093"	3"	0.093"
3"x3"x1/8"	3"	0.125"
4"x4"x1/8"	4"	0.125"
6"x6"x1/8"	6"	0.125"




F 3" FLUTED POST



G 3" - 6" U-CLIP

U-CLIP SCHEDULE:


CLIP SIZE	L	W	S1	S2
3" U-CLIP	2.625"	2.500"	1.500"	1.625"
4" U-CLIP	3.625"	3.375"	2.375"	2.625"
6" U-CLIP	5.625"	5.000"	3.500"	3.625"




H 4" FLUTED POST

CLIP SCHEDULE:

BEAM TYPE	L	tb
3"x1/4"	3"	0.250"
4"x1/4"	4"	0.250"



I CLIP ANGLE



J 3" - 6" EXTENDED U-CLIP

EXTENDED U-CLIP  
SCHEDULE:

CLIP SIZE	L1	L2	W	S1	S2
3" U-CLIP	2.625"	5.310"	2.750"	1.500"	2.155"
4" U-CLIP	3.625"	6.500"	3.375"	2.125"	2.750"
6" U-CLIP	5.625"	8.310"	5.750"	4.500"	3.655"

STRUCTALL BUILDING SYSTEMS, INC.  
350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627  
INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FB/C 2023 (23-69317)	CLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25


THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS,  
AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT  
WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS,  
ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT  
PERMITTED AND INVALIDATE OUR CERTIFICATION.



ROOF CONNECTIONS


COPIES WITHOUT  
ORIGINAL PE SEAL NOT  
VALID FOR PERMIT

SPACE RESERVED FOR  
CERTIFYING ENGINEER'S  
DIGITAL OR PHYSICAL SEAL  
& DATE OF CERTIFICATION



1  
4  
3" = 1'-0"


ROOF PANEL TO EAVE BEAM



2  
4  
3" = 1'-0"

ROOF PANEL GUTTER DETAIL


SECTION



3  
4  
3" = 1'-0"

ROOF PANEL TO WOOD  
HOST STRUCTURE

SECTION



4  
4  
3" = 1'-0"

ROOF PANEL TO CONC. OR  
BLOCK HOST STRUCTURE

SECTION

**DIGITAL SEAL NOTICE:**  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS  
ITEM HAS BEEN DIGITALLY SIGNED BY THE  
ABOVE-SIGNING ENGINEER ON THE DATE  
ADJACENT TO THE SEAL. PRINTED COPIES OF THIS  
DOCUMENT ARE NOT CONSIDERED SIGNED AND  
SEALED AND THE SIGNATURE MUST BE VERIFIED  
ON ANY ELECTRONIC COPIES.  
VISIT [E.C.A.L.C./D/S](http://E.C.A.L.C./D/S) FOR MORE INFORMATION.  
**PRINTED DOCUMENT NOTICE:**  
IF THIS DOCUMENT IS PRINTED & DOES NOT  
CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE &  
SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR  
USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
**VALID FOR 1 PERMIT ONLY U.N.O.**

**ENGINEERING  
EXPRESS®**  
POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
[ENGINEERINGEXPRESS.COM](http://ENGINEERINGEXPRESS.COM)

STRUCTALL BUILDING SYSTEMS, INC.  
350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627  
INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FBC 2023 (23-69317)	CLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS,  
AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT  
WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS,  
ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT  
PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

23-69317

SCALE: NTS UNLESS NOTED


ALEXANDRACQUINALEXANDRACOLVINENGINEERING EXPRESS/production - documents/projects/23-123-69317 2023 fbc update structural insulated patio cover over open wallwork/drawings & cad/23-6931 7c - structural mps open room systems.dwg

## 5 9



FREESTANDING SYSTEM & HOST-ATTACHED ALLOWABLE POST HEIGHT

COLUMN TYPE	MAX ROOF SPAN S (FT)	GRAVITY/UPLIFT ASD DESIGN LOAD (PSF)	LATERAL ASD WIND LOAD (PSF)	MAXIMUM COLUMN SPACING (FT)					
				6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	15'-0"
				ALLOWABLE POST HEIGHT (FT)					
3"x3" Fluted Post (Unbraced) 10ft	12'-0"	10 PSF	20 PSF	8'-5"	4'-5"	-	-	-	-
			30 PSF	6'-10"	-	-	-	-	-
			40 PSF	6'-0"	-	-	-	-	-
			50 PSF	5'-4"	-	-	-	-	-
		20 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		30 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
	15'-0"	40 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		10 PSF	20 PSF	6'-4"	-	-	-	-	-
			30 PSF	5'-2"	-	-	-	-	-
			40 PSF	4'-6"	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		20 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		30 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		40 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-



- TABLE NOTES:
- 1) 2015 ALUMINUM DESIGN MANUAL, ALLOWABLE STRESS DESIGN METHOD USED IN ALL TABLES.
  - 2) MAXIMUM ALLOWABLE POST HEIGHT IS 10 FT.
  - 3) DEFLECTION LIMIT = L/120.
  - 4) COLUMN SPACING IS HALF THE DISTANCE TO THE LEFT ADDED TO HALF THE DISTANCE TO THE RIGHT OF THE BEAM (AVERAGE COLUMN SPACING).
  - 5) VALUES BELOW ALLOWABLE CEILING HEIGHT INTENDED TO BE BUILT ON KNEEWALLS OR OTHER SUPPORTING STRUCTURES (CERTIFIED BY OTHERS).
  - 6) 2PSF DEAD LOAD USED IN CALCULATIONS.
  - 7) POSITIVE AND NEGATIVE DESIGN PRESSURES CALCULATED FOR USE WITH THIS SYSTEM SHALL BE DETERMINED BY OTHERS ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH ASCE 7-22 OR ASCE 7-16 BASED ON APPLICABLE CODE.

COLUMN TYPE	MAX ROOF SPAN S (FT)	GRAVITY/UPLIFT ASD DESIGN LOAD (PSF)	LATERAL ASD WIND LOAD (PSF)	MAXIMUM COLUMN SPACING (FT)					
				6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	15'-0"
				ALLOWABLE POST HEIGHT (FT)					
3"x3"x0.093" Post (Unbraced) 10ft	12'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	7'-11"	5'-4"	4'-3"
			30 PSF	10'-0"	10'-0"	9'-0"	6'-5"	4'-4"	-
			40 PSF	10'-0"	10'-0"	7'-9"	5'-7"	-	-
			50 PSF	10'-0"	9'-5"	7'-0"	5'-0"	-	-
		20 PSF	20 PSF	10'-0"	4'-5"	-	-	-	-
			30 PSF	9'-1"	-	-	-	-	-
			40 PSF	7'-11"	-	-	-	-	-
			50 PSF	7'-1"	-	-	-	-	-
		30 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
	15'-0"	10 PSF	20 PSF	10'-0"	10'-0"	8'-6"	5'-2"	-	-
			30 PSF	10'-0"	10'-0"	7'-0"	4'-3"	-	-
			40 PSF	10'-0"	9'-0"	6'-0"	-	-	-
			50 PSF	10'-0"	8'-0"	5'-4"	-	-	-
		20 PSF	20 PSF	7'-4"	-	-	-	-	-
			30 PSF	6'-0"	-	-	-	-	-
			40 PSF	5'-2"	-	-	-	-	-
			50 PSF	4'-7"	-	-	-	-	-
		30 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		40 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-

COLUMN TYPE	MAX ROOF SPAN S (FT)	GRAVITY/UPLIFT ASD DESIGN LOAD (PSF)	LATERAL ASD WIND LOAD (PSF)	MAXIMUM COLUMN SPACING (FT)					
				6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	15'-0"
				ALLOWABLE POST HEIGHT (FT)					
3"x3" Fluted Post (Unbraced) 10ft	12'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-9"	8'-7"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	8'-0"	7'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	8'-9"	6'-11"	6'-1"
			50 PSF	10'-0"	10'-0"	9'-11"	7'-10"	6'-2"	5'-5"
		20 PSF	20 PSF	10'-0"	10'-0"	5'-5"	-	-	-
			30 PSF	10'-0"	8'-8"	4'-5"	-	-	-
			40 PSF	10'-0"	7'-6"	-	-	-	-
			50 PSF	10'-0"	6'-8"	-	-	-	-
		30 PSF	20 PSF	9'-7"	-	-	-	-	-
			30 PSF	7'-10"	-	-	-	-	-
			40 PSF	6'-9"	-	-	-	-	-
			50 PSF	6'-1"	-	-	-	-	-
	15'-0"	10 PSF	20 PSF	-	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	7'-2"	5'-11"
			30 PSF	10'-0"	10'-0"	10'-0"	8'-2"	5'-10"	4'-10"
			40 PSF	10'-0"	10'-0"	9'-6"	7'-1"	5'-1"	4'-2"
			50 PSF	10'-0"	10'-0"	8'-6"	6'-4"	4'-6"	-
		30 PSF	20 PSF	10'-0"	6'-8"	-	-	-	-
			30 PSF	10'-0"	5'-5"	-	-	-	-
			40 PSF	10'-0"	4'-9"	-	-	-	-
			50 PSF	9'-0"	4'-3"	-	-	-	-
		40 PSF	20 PSF	4'-6"	-	-	-	-	-
			30 PSF	-	-	-	-	-	-
			40 PSF	-	-	-	-	-	-
			50 PSF	-	-	-	-	-	-

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

\*THIS DETAIL APPLIES TO BOTH HOST ATTACHED AND FREE-STANDING ROOF OVER OPEN STRUCTURES

POST SPACING ISOMETRIC

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

DIGITAL SEAL NOTICE: IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES. VISIT ECALC.IO/DS FOR MORE INFORMATION. PRINTED DOCUMENT NOTICE: IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE. VALID FOR 1 PERMIT ONLY U.N.O.

ENGINEERING EXPRESS

POSTAL ADDRESS: 2234 NORTH FEDERAL HWY #7664 BOCA RATON, FL 33431 ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC.

350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627

INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FBCC 2023 (23-69317)	GLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25
THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.			

COPYRIGHT ENGINEERING EXPRESS®

23-69317

SCALE: NTS UNLESS NOTED

6

OF


7/25/2025 9:30 AM ALEXANDRA COLEMAN\alexandracoleman\engineering\express\production - documents\projects\23-123-69317 2023 fbc update structural insulated patio cover over open wall\work\drawings & cad\23-69317c - structural mps open room systems.dwg

FREESTANDING SYSTEM & HOST-ATTACHED ALLOWABLE WIND LOAD POST HEIGHT - CONTINUED

COLUMN TYPE	MAX ROOF SPAN S (FT)	GRAVITY/UPLIFT ASD DESIGN LOAD (PSF)	LATERAL ASD WIND LOAD (PSF)	MAXIMUM COLUMN SPACING (FT)					
				6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	15'-0"
				ALLOWABLE POST HEIGHT (FT)					
4"x4" Fluted Post (Unbraced) 10ft	12'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-6"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-9"	8'-8"	8'-3"
			50 PSF	10'-0"	10'-0"	10'-0"	8'-9"	7'-9"	7'-4"
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	8'-9"	8'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	8'-7"	7'-2"	6'-6"
			40 PSF	10'-0"	10'-0"	9'-0"	7'-5"	6'-2"	5'-8"
			50 PSF	10'-0"	9'-10"	8'-1"	6'-8"	5'-6"	5'-0"
		30 PSF	20 PSF	10'-0"	10'-0"	9'-9"	7'-3"	5'-3"	4'-4"
			30 PSF	10'-0"	10'-0"	8'-0"	6'-0"	4'-3"	-
			40 PSF	10'-0"	9'-2"	6'-11"	5'-2"	-	-
			50 PSF	10'-0"	8'-2"	6'-2"	4'-7"	-	-
		40 PSF	20 PSF	10'-0"	10'-0"	6'-9"	4'-0"	-	-
			30 PSF	10'-0"	8'-4"	5'-6"	-	-	-
			40 PSF	10'-0"	7'-3"	4'-10"	-	-	-
			50 PSF	9'-5"	6'-6"	4'-3"	-	-	-
	15'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-5"	8'-10"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-3"	8'-2"	7'-8"
			50 PSF	10'-0"	10'-0"	9'-6"	8'-3"	7'-3"	6'-10"
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	9'-2"	7'-3"	6'-5"
			30 PSF	10'-0"	10'-0"	9'-4"	7'-6"	6'-0"	5'-3"
			40 PSF	10'-0"	10'-0"	8'-1"	6'-6"	5'-1"	4'-6"
			50 PSF	10'-0"	9'-2"	7'-3"	5'-9"	4'-7"	4'-1"
		30 PSF	20 PSF	10'-0"	10'-0"	7'-10"	5'-2"	-	-
			30 PSF	10'-0"	9'-2"	6'-5"	4'-3"	-	-
			40 PSF	10'-0"	8'-0"	5'-7"	-	-	-
			50 PSF	10'-0"	7'-1"	5'-0"	-	-	-
		40 PSF	20 PSF	10'-0"	8'-0"	4'-3"	-	-	-
			30 PSF	10'-0"	6'-6"	-	-	-	-
			40 PSF	9'-2"	5'-8"	-	-	-	-
			50 PSF	8'-2"	5'-0"	-	-	-	-

COLUMN TYPE	MAX ROOF SPAN S (FT)	GRAVITY/UPLIFT ASD DESIGN LOAD (PSF)	LATERAL ASD WIND LOAD (PSF)	MAXIMUM COLUMN SPACING (FT)					
				6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	15'-0"
				ALLOWABLE POST HEIGHT (FT)					
6"x6"x1/8" Post (Unbraced) 10ft	12'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-7"	9'-2"
			50 PSF	10'-0"	10'-0"	10'-0"	9'-3"	8'-6"	8'-3"
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-3"	8'-10"
			50 PSF	10'-0"	10'-0"	10'-0"	9'-0"	8'-3"	8'-0"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-10"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-9"	9'-0"	8'-7"
			50 PSF	10'-0"	10'-0"	9'-9"	8'-9"	8'-4"	7'-8"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-6"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-6"	8'-7"	8'-3"
			50 PSF	10'-0"	10'-0"	9'-6"	8'-6"	7'-8"	7'-4"
	15'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-6"	9'-2"	9'-2"
			50 PSF	10'-0"	10'-0"	10'-0"	9'-2"	8'-6"	8'-2"
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-1"	8'-9"	8'-9"
			50 PSF	10'-0"	10'-0"	9'-10"	8'-11"	8'-2"	7'-10"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-8"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-7"	8'-9"	8'-4"
			50 PSF	10'-0"	10'-0"	9'-7"	8'-7"	7'-10"	7'-6"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	9'-2"	9'-2"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-3"	8'-4"	8'-0"
			50 PSF	10'-0"	10'-0"	9'-3"	8'-3"	7'-5"	7'-1"

COLUMN TYPE	MAX ROOF SPAN S (FT)	GRAVITY/UPLIFT ASD DESIGN LOAD (PSF)	LATERAL ASD WIND LOAD (PSF)	MAXIMUM COLUMN SPACING (FT)					
				6'-0"	8'-0"	10'-0"	12'-0"	14'-0"	15'-0"
				ALLOWABLE POST HEIGHT (FT)					
4"x4"x1/8" Post (Unbraced) 10ft	12'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			50 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			50 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-4"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-6"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	7'-9"	7'-9"
			40 PSF	10'-0"	10'-0"	10'-0"	9'-5"	6'-9"	5'-6"
			50 PSF	10'-0"	10'-0"	10'-0"	8'-5"	6'-0"	5'-0"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	7'-2"	-	-
			30 PSF	10'-0"	10'-0"	10'-0"	5'-10"	-	-
			40 PSF	10'-0"	10'-0"	8'-9"	5'-1"	-	-
			50 PSF	10'-0"	10'-0"	7'-10"	4'-6"	-	-
	15'-0"	10 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			40 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			50 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
		20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"	9'-7"
			40 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-5"	8'-4"
			50 PSF	10'-0"	10'-0"	10'-0"	10'-0"	8'-5"	7'-5"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	9'-4"	5'-2"	-
			30 PSF	10'-0"	10'-0"	10'-0"	7'-8"	4'-3"	-
			40 PSF	10'-0"	10'-0"	10'-0"	6'-8"	-	-
			50 PSF	10'-0"	10'-0"	9'-1"	6'-0"	-	-
		40 PSF	20 PSF	10'-0"	10'-0"	7'-6"	-	-	-
			30 PSF	10'-0"	10'-0"	6'-2"	-	-	-
			40 PSF	10'-0"	10'-0"	5'-4"	-	-	-
			50 PSF	10'-0"	9'-2"	4'-9"	-	-	-



\*THIS DETAIL APPLIES TO BOTH HOST ATTACHED AND FREE-STANDING ROOF OVER OPEN STRUCTURES

POST SPACING ISOMETRIC

- TABLE NOTES:
- 1) 2015 ALUMINUM DESIGN MANUAL, ALLOWABLE STRESS DESIGN METHOD USED IN ALL TABLES.
  - 2) MAXIMUM ALLOWABLE POST HEIGHT IS 10 FT.
  - 3) DEFLECTION LIMIT = L/120.
  - 4) COLUMN SPACING IS HALF THE DISTANCE TO THE LEFT ADDED TO HALF THE DISTANCE TO THE RIGHT OF THE BEAM (AVERAGE COLUMN SPACING).
  - 5) VALUES BELOW ALLOWABLE CEILING HEIGHT INTENDED TO BE BUILT ON KNEEWALLS OR OTHER SUPPORTING STRUCTURES (CERTIFIED BY OTHERS).
  - 6) 2PSF DEAD LOAD USED IN CALCULATIONS.
  - 7) POSITIVE AND NEGATIVE DESIGN PRESSURES CALCULATED FOR USE WITH THIS SYSTEM SHALL BE DETERMINED BY OTHERS ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH ASCE 7-22 OR ASCE 7-16 BASED ON APPLICABLE CODE.

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [E.CALC.IO/DS](http://E.CALC.IO/DS) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
VALID FOR 1 PERMIT ONLY U.S.A.

ENGINEERING EXPRESS

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC.

350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627

INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FBC 2023 (23-69317)	CLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25
THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.			

COPYRIGHT ENGINEERING EXPRESS

23-69317

SCALE: NTS UNLESS NOTED


FREESTANDING & HOST ATTACHED SYSTEM EAVE BEAM SPANS

Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x4" SMB Beam	20 PSF	7'-0"	6'-5"	6'-0"	5'-7"	5'-3"	
	30 PSF	5'-9"	5'-3"	4'-10"	4'-6"	4'-3"	
	40 PSF	5'-0"	4'-6"	4'-2"	4'-0"	3'-8"	
	50 PSF	4'-5"	4'-1"	3'-9"	3'-6"	3'-4"	

Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x5" SMS Beam	20 PSF	8'-4"	7'-8"	7'-1"	6'-7"	6'-3"	
	30 PSF	6'-10"	6'-3"	5'-9"	5'-5"	5'-1"	
	40 PSF	6'-0"	5'-5"	5'-0"	4'-8"	4'-5"	
	50 PSF	5'-4"	4'-10"	4'-6"	4'-2"	4'-0"	


Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x6" SMS Beam	20 PSF	10'-7"	9'-8"	9'-0"	8'-4"	7'-11"	
	30 PSF	8'-8"	7'-11"	7'-3"	6'-10"	6'-5"	
	40 PSF	7'-6"	6'-10"	6'-4"	5'-11"	5'-7"	
	50 PSF	6'-8"	6'-1"	5'-8"	5'-3"	5'-0"	

Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x7" SMS Beam	20 PSF	10'-11"	10'-0"	9'-2"	8'-7"	8'-1"	
	30 PSF	8'-11"	8'-1"	7'-6"	7'-0"	6'-7"	
	40 PSF	7'-8"	7'-0"	6'-6"	6'-1"	5'-9"	
	50 PSF	6'-11"	6'-3"	5'-10"	5'-5"	5'-2"	



\*THIS DETAIL APPLIES TO BOTH HOST ATTACHED AND FREE-STANDING ROOF OVER OPEN STRUCTURES

EAVE-BEAM SPACING ISOMETRIC



- TABLE NOTES:
- 2015 ALUMINUM DESIGN MANUAL, ALLOWABLE STRESS DESIGN METHOD USED IN ALL TABLES.
  - DEFLECTION LIMIT = L/120
  - 2PSF DEAD LOAD CONSIDERED IN CALCULATIONS.
  - POSITIVE AND NEGATIVE DESIGN PRESSURES CALCULATED FOR USE WITH THIS SYSTEM SHALL BE DETERMINED BY OTHERS ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH ASCE 7-22 OR ASCE 7-16 BASED ON APPLICABLE CODE.

Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x8" SMS Beam	20 PSF	15'-0"	15'-0"	14'-6"	13'-6"	12'-9"	
	30 PSF	14'-0"	12'-9"	11'-10"	11'-1"	10'-5"	
	40 PSF	12'-1"	11'-1"	10'-3"	9'-7"	9'-0"	
	50 PSF	10'-10"	9'-11"	9'-2"	8'-7"	8'-1"	

Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x9" SMS Beam	20 PSF	15'-0"	15'-0"	15'-0"	15'-0"	14'-2"	
	30 PSF	15'-0"	14'-2"	13'-1"	12'-3"	11'-7"	
	40 PSF	13'-5"	12'-3"	11'-4"	10'-8"	10'-0"	
	50 PSF	12'-0"	11'-0"	10'-2"	9'-6"	9'-0"	

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [EALC.IQ/DS](http://EALC.IQ/DS) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
VALID FOR 1 PERMIT ONLY U.S.A.

ENGINEERING EXPRESS

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC.

350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627

INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (20-25226)	TT	FB	05/28/20
REVISION (20-25226)	AEM	FB	10/08/20
FBC 2023 (23-69317)	CLV	CCB	12/19/23
ADD 2X8 BEAM	CCB	CCB	2/04/25
ADD COMPONENTS	ANC	CCB	7/23/25

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®


23-69317

SCALE: NTS UNLESS NOTED






FREESTANDING & HOST ATTACHED SYSTEM EAVE BEAM SPANS




Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x10" SMB Beam	20 PSF	15'-0"	15'-0"	15'-0"	15'-0"	15'-0"	
	30 PSF	15'-0"	15'-0"	15'-0"	15'-0"	15'-0"	
	40 PSF	15'-0"	15'-0"	15'-0"	15'-0"	14'-2"	
	50 PSF	15'-0"	15'-0"	14'-4"	13'-5"	12'-8"	

2"x10" SELF MATING BEAM




Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x8" Edge Beam	20 PSF	15'-0"	15'-0"	15'-0"	15'-0"	15'-0"	
	30 PSF	15'-0"	15'-0"	14'-6"	13'-7"	12'-9"	
	40 PSF	14'-10"	13'-7"	12'-6"	11'-9"	11'-1"	
	50 PSF	13'-3"	12'-1"	11'-3"	10'-6"	9'-7"	

2"x8" EDGE BEAM




Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x5" Edge Beam	20 PSF	12'-7"	11'-6"	10'-8"	10'-0"	9'-5"	
	30 PSF	10'-3"	9'-5"	8'-8"	8'-1"	7'-8"	
	40 PSF	8'-11"	8'-1"	7'-6"	7'-0"	6'-8"	
	50 PSF	8'-0"	7'-3"	6'-9"	6'-3"	6'-0"	

2"x5" EDGE BEAM



Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x7" Edge Beam	20 PSF	15'-0"	15'-0"	15'-0"	14'-3"	13'-5"	
	30 PSF	14'-9"	13'-5"	12'-5"	11'-8"	11'-0"	
	40 PSF	12'-9"	11'-8"	10'-9"	10'-1"	9'-6"	
	50 PSF	11'-5"	10'-5"	9'-8"	9'-0"	8'-6"	

2"x7" EDGE BEAM




Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x7" Reinforced Edge Beam	20 PSF	15'-0"	15'-0"	15'-0"	15'-0"	15'-0"	
	30 PSF	15'-0"	15'-0"	15'-0"	14'-2"	13'-5"	
	40 PSF	15'-0"	14'-2"	13'-2"	12'-4"	11'-7"	
	50 PSF	13'-11"	12'-8"	11'-9"	11'-0"	10'-4"	

2"x7" REINFORCED EDGE BEAM


COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION





Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x10" Edge Beam	20 PSF	15'-0"	15'-0"	15'-0"	15'-0"	15'-0"	
	30 PSF	15'-0"	15'-0"	15'-0"	15'-0"	15'-0"	
	40 PSF	15'-0"	15'-0"	15'-0"	14'-1"	13'-3"	
	50 PSF	15'-0"	14'-6"	13'-5"	12'-7"	11'-9"	

2"x10" EDGE BEAM



Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
6.7 C-Beam	20 PSF	14'-2"	13'-0"	12'-0"	11'-2"	10'-7"	
	30 PSF	11'-7"	10'-7"	9'-9"	9'-2"	8'-7"	
	40 PSF	10'-0"	9'-2"	8'-5"	7'-11"	7'-5"	
	50 PSF	9'-0"	8'-2"	7'-7"	7'-1"	6'-8"	

6.7 C-BEAM



Beam Type	Roof Load (psf)	Max Roof Span (ft)					Max Beam Span (ft)
		8'-0"	10'-0"	12'-0"	14'-0"	16'-0"	
2"x4" Tilt Beam	20 PSF	7'-7"	6'-11"	6'-5"	6'-0"	5'-8"	
	30 PSF	6'-2"	5'-8"	5'-3"	4'-10"	4'-7"	
	40 PSF	5'-4"	4'-10"	4'-6"	4'-3"	4'-0"	
	50 PSF	4'-9"	4'-4"	4'-0"	3'-9"	3'-7"	

4" TILT BEAM

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT ECALC.COM/DS FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
VALID FOR 1 PERMIT ONLY U.S.A.

STRUCTALL BUILDING SYSTEMS, INC.  
350 BURBANK RD  
OLDSMAR, FL 34677  
(813) 855-2627

INSULATED PATIO COVER  
ROOF OVER OPEN WALL ROOM SYSTEMS  
PERFORMANCE EVALUATION

ENGINEERING EX-EXPRESS®  
POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
ENGINEERINGEXPRESS.COM

REMARKS  
ORIGINAL PROJECT (20-25226)  
REVISION (20-25226)  
FBC 2023 (23-69317)  
ADD 2X8 BEAM  
ADD COMPONENTS

DATE  
05/28/20  
10/08/20  
12/19/23  
2/04/25  
7/23/25

DRWN  
TT  
AEM  
CLV  
ANC

CHKD  
FB  
FB  
CCB  
CCB

COPYRIGHT ENGINEERING EXPRESS®  
23-69317  
SCALE: NTS UNLESS NOTED  
OF