



# 3" MODULAR ROOMS GLASS WALL ROOM SYSTEM PERFORMANCE EVALUATION

- THIS ENCLOSURE IS ONLY CERTIFIED AS **NON-HABITABLE** PER AAMA 2100


- THIS ENCLOSURE DOES NOT QUALIFY FOR LARGE MISSILE IMPACT RESISTANCE UNDER ANY CIRCUMSTANCE

THIS IS A NON-SITE-SPECIFIC PERFORMANCE EVALUATION. A DESIGN PROFESSIONAL SHALL BE RESPONSIBLE FOR CERTIFYING THE APPLICATION OF THIS INFORMATION TO ANY SITE-SPECIFIC LOCATION.

ATTACHMENT OF GLAZING PRODUCTS TO MULLIONS TO BE PER SEPARATE PRODUCT ENGINEERING BY OTHERS

3" SNAP-N-LOCK COMPOSITE PANEL PER SEPARATE APPROVAL

EXISTING HOST STRUCTURE BY OTHERS, TYP.




EXISTING 3KSI CONCRETE SLAB OR WOOD DECK (G=0.55 MIN. WOOD) BY OTHERS, TYP.

1 MODULAR ROOM ISOMETRIC  
2 N.T.S. EXPLODED ISOMETRIC

VISIT [ECALC.IO/STRUCTALL](https://ecalc.io/structall)

FOR ENGINEER CERTIFIED ORIGINALS & MORE INFORMATION ABOUT THIS DOCUMENT OR SCAN THE QR CODE TO THE RIGHT >

VISIT [ENGINEERINGEXPRESS.COM/STORE](https://engineeringexpress.com/store) FOR ADDITIONAL PLANS, REPORTS & RESOURCES



NOTE : THIS DOCUMENT IS NOT TO BE USED WITHOUT AN ORIGINAL PEN SIGNATURE & RAISED SEAL OR ELECTRONICALLY VERIFIABLE ELECTRONIC SIGNATURE MEETING ALL DISCLAIMERS SET FORTH HEREIN. RUBBED PENCIL COPIES ARE NOT PERMITTED FOR USE IN ANY WAY

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

## DESIGN NOTES:

POSITIVE AND NEGATIVE DESIGN PRESSURES CALCULATED FOR USE WITH THIS SYSTEM SHALL BE DETERMINED BY OTHERS ON A JOB-SPECIFIC BASIS IN ACCORDANCE WITH THE STRUCTURAL REQUIREMENTS OF THE FLORIDA BUILDING CODE 7TH (2020) & 8TH (2023) EDITIONS AND THE 2021/2018 IBC/IRC, AS WELL AS CURRENT VERSIONS OF THE MN, NC, NJ, NY, OH, SC, & VA BUILDING CODES AS APPLICABLE. CODE ENFORCED COMPLIES WITH STATE OF SEAL AND IF MULTIPLE VERSIONS LISTED THEN MOST STRINGENT APPLIES. DESIGN SHALL UTILIZE ASD DESIGN METHOD USING ASCE 7-16 OR ASCE 7-22 BASED.

\*THIS DOCUMENT DOES **NOT** CERTIFY PRODUCT FOR USE AS A HABITABLE STRUCTURE. AAMA 2100 SUNROOM CLASSIFICATION II, III, OR IV ONLY.

## GENERAL NOTES:

- STRUCTURE SHALL BE FABRICATED IN ACCORDANCE WITH ALL GOVERNING CODES. CONTRACTOR SHALL INVESTIGATE AND CONFORM TO ALL LOCAL BUILDING CODE AMENDMENTS WHICH MAY APPLY.
- NO 33-1/3% INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE DESIGN OF THIS SYSTEM.
- THE ARCHITECT/ENGINEER OF RECORD OR PERMITTING CONTRACTOR FOR THE PROJECT SHALL BE RESPONSIBLE FOR THE INTEGRITY OF ALL SUPPORTING SURFACES.
- THE HOST STRUCTURE SHALL NOT BE MODIFIED WITH THIS DESIGN - ALL EXISTING WINDOWS, DOORS, AND WALLS SHALL REMAIN IN PLACE. WHERE IMPACT PROTECTION IS REQUIRED, IT SHALL BE PLACED AT THE HOST STRUCTURE, NOT ON THE SUNROOM.
- ANCHORAGE**  
ALL FASTENERS TO BE #12 OR GREATER SAE GRADE 5 UNLESS NOTED OTHERWISE. FASTENERS SHALL BE CADMIUM-PLATED OR OTHERWISE CORROSION-RESISTANT MATERIAL AND SHALL COMPLY WITH "SPECIFICATIONS FOR ALUMINUM STRUCTURES" SECTION J.3.1 BY THE ALUMINUM ASSOCIATION, INC., & ANY APPLICABLE FEDERAL, STATE, AND/OR LOCAL CODES.
- ANCHORS SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURERS' RECOMMENDATIONS. MINIMUM EMBEDMENT SHALL BE AS NOTED HEREIN. MINIMUM EMBEDMENT AND EDGE DISTANCE EXCLUDES STUCCO, FOAM, BRICK, AND OTHER WALL FINISHES.
- ALL CONCRETE ANCHORS SHALL BE INSTALLED TO NON-CRACKED CONCRETE ONLY.
- MATERIALS**  
THE CONTRACTOR IS RESPONSIBLE TO INSULATE ALL MEMBERS FROM DISSIMILAR MATERIALS TO PREVENT ELECTROLYSIS.
- ALL ALUMINUM SHALL BE 6063-T6 ALLOY AND TEMPER UNLESS NOTED OTHERWISE.
- ALL CONCRETE TO REACH A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI IN 7 DAYS.
- ANY WOOD USED IN A PRIMARY CONNECTION SHALL BE SYP#2 OR BETTER.
- OTHER**  
ENGINEER SEAL AFFIXED HERETO VALIDATES STRUCTURAL DESIGN AS SHOWN ONLY. USE OF THIS SPECIFICATION BY CONTRACTOR, et. al. INDEMNIFIES & SAVES HARMLESS THIS ENGINEER FOR ALL COST & DAMAGES INCLUDING LEGAL FEES & APPELLATE FEES RESULTING FROM MATERIAL FABRICATION, SYSTEM ERECTION, & CONSTRUCTION PRACTICES BEYOND THAT WHICH IS CALLED FOR BY LOCAL, STATE, & FEDERAL CODES & FROM DEVIATIONS OF THIS PLAN.
- THIS ENGINEER HAS NOT VISITED THIS JOBSITE. INFORMATION CONTAINED HEREIN IS BASED ON CONTRACTOR SUPPLIED DATA AND MEASUREMENTS. THIS ENGINEER SHALL NOT BE HELD RESPONSIBLE OR LIABLE IN ANY WAY FOR ERRONEOUS OR INACCURATE DATA OR MEASUREMENTS. WORK SHALL BE FIELD VERIFIED PRIOR TO CONSTRUCTION. THIS ENGINEER SHALL BE NOTIFIED AND GIVEN AN OPPORTUNITY TO REEVALUATE OUR WORK UPON DISCOVERY OF ANY INACCURATE INFORMATION PRIOR TO MODIFICATION OF EXISTING FIELD CONDITIONS AND FABRICATION AND INSTALLATION OF MATERIALS.
- EXCEPT AS EXPRESSLY PROVIDED HEREIN, NO ADDITIONAL CERTIFICATIONS OR AFFIRMATIONS ARE INTENDED.
- ALTERATIONS, ADDITIONS OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE THIS CERTIFICATION.

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [ECALC.IO/IDS](https://ecalc.io/ids) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE. VALID FOR 1 PERMIT ONLY UNLESS NOTED OTHERWISE.

ENGINEERING EXPRESS

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
[ENGINEERINGEXPRESS.COM](https://engineeringexpress.com)

STRUCTALL BUILDING SYSTEMS, INC

350 BURBANK RD  
OLDSMAR, FL  
(813) 855-2627

3 IN MODULAR GLASS  
GLASS ROOM WITH MONOSLOPE ROOF  
PERFORMANCE EVALUATION



REMARKS	DATE	DRWN	CHKD
ORIGINAL PROJECT (20-2544)	5/29/20	TT	FLB
2021 REVISIONS (UPDATE 00-2544)	11/03/21	OCB	FLB
2023 FBC (23-69327)	01/05/23	CLV	OCB

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®  
23-69327


SCALE: NTS UNLESS NOTED

EXTRUSIONS




ELEVATION TYPICAL FOR MODULAR ROOMS WITH GLAZING PRODUCTS

1 SLOPED ROOF  
2 N.T.S. PLAN VIEW



2 SLOPED ROOF  
2 N.T.S. SIDE ELEVATION



3 SLOPED ROOF  
2 N.T.S. FRONT ELEVATION

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [EALC.I/O/DS](http://EALC.I/O/DS) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE. VALID FOR 1 PERMIT ONLY U.N.O.

**ENGINEERING EXPRESS**  
POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
[ENGINEERINGEXPRESS.COM](http://ENGINEERINGEXPRESS.COM)

STRUCTALL BUILDING SYSTEMS, INC  
350 BURBANK RD  
OLDSMAR, FL  
(813) 855-2627  
3 IN MODULAR GLASS  
GLASS ROOM WITH MONOSLOPE ROOF  
PERFORMANCE EVALUATION

REMARKS	DATE	DRWN	CHKD
ORIGINAL PROJECT 00-29344	5/29/20	TT	FLB
2021 FORMATTING UPDATE 00-29344	11/03/21	OCB	FLB
2023 FBC (23-69327)	01/05/23	CLV	OCB

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.



CONNECTIONS

CONNECTION TO EXISTING WOOD TRUSS OR RAFTER WITH FASCIA BOARD / SOFFIT (G=0.55 MIN WOOD, BY OTHERS).

PROVIDE PAIRS OF (2)-#14 WOOD SCREWS INTO EACH STRUCTURAL ROOF RAFTER (ANCHOR PAIRS SPACED MAX 24" O.C.) WITH 2 1/2" THREAD PENETRATION INTO STRUCTURAL MEMBER OR BLOCKING. MAINTAIN 3/4" EDGE DISTANCE. MAX ALLOWABLE DESIGN SHEAR = 160 PLF

FOR HIGHER DESIGN LOADING, INCLUDE ADDITIONAL PAIRS OF ANCHORS @ 12" O.C. INTO FASCIA BOARD. MAX ALLOWABLE DESIGN SHEAR = 320 PLF

EXISTING WOOD ROOF RAFTERS & FASCIA (G=0.55 MIN.) WOOD, TYP.

#12 SAE GRADE 5 SHEET METAL SCREWS AT 12" O.C. EA SIDE, TYP.

3" SNAP-N-LOCK COMPOSITE PANEL PER SEPARATE ENG

CONNECTION TO STRUCTUTAL WOOD FRAMED WALL, WITH ADDITIONAL BLOCKING AS NECESSARY (G=0.55 MIN WOOD, BY OTHERS).

PROVIDE PAIRS OF (2)-#14 WOOD SCREWS (OR 1/4" Ø TAPCONS) WITH WASHERS INTO EACH STRUCTURAL WALL STUDS OR BLOCKING (ANCHOR PAIRS SPACED MAX 16" O.C.) WITH 2 1/2" THREAD PENETRATION INTO STRUCTURAL MEMBER OR BLOCKING. MAINTAIN 3/4" EDGE DISTANCE. MAX ALLOWABLE DESIGN SHEAR = 250 PLF

STRUCTURAL WOOD FRAME WALL WITH ADDITIONAL STRUCTURAL BLOCKING AS REQUIRED (BY OTHERS)

3" SNAP-N-LOCK COMPOSITE PANEL PER SEPARATE ENG

ALTERNATE PANEL CONNECTION OPTION: USE 1/4" Ø SAE GRADE 5 SEX BOLTS AT 18" O.C. AND 4" FROM ENDS, TYP.

USE (1) 1/4"Ø OR 3/8"Ø ITW TAPCON SCREW ANCHOR WITH 1"Ø WASHER (OR MNFR'S EQUIVALENT) @ 16" O.C. WITH 1 3/4" EMBED TO 3 KSI CONCRETE, OR HOLLOW / GROUTED CMU BLOCK. MAINTAIN 2 1/2" EDGE DIST & 1 ANCHOR PER BLOCK CELL, MAX LED BLOCK, 2 1/2" EDGE DIST.

MAX ALLOWABLE DESIGN SHEAR TO GROUTED CMU BLOCK WITH 1/4" Ø ANCHORS = 125 PLF

MAX ALLOWABLE DESIGN SHEAR TO 3 KSI CONCRETE, OR GROUTED / HOLLOW CMU BLOCK WITH 3/8" Ø ANCHORS = 400 PLF

EXISTING 3KSI CONCRETE, OR HOLLOW / GROUTED CMU BLOCK (PER ASTM C-90) HOST STRUCTURE

#12 SAE GRADE 5 SHEET METAL SCREWS AT 12" O.C. EA SIDE, TYP.

3" SNAP-N-LOCK COMPOSITE PANEL PER SEPARATE ENG

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

DIGITAL SEAL NOTICE: IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES. VISIT EOL.CA/DOCS FOR MORE INFORMATION. PRINTED DOCUMENT NOTICE: IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE. VALID FOR 1 PERMIT ONLY UNLESS OTHERWISE NOTED.

ENGINEERING EXPRESS

POSTAL ADDRESS: 2234 NORTH FEDERAL HWY #7664 BOCA RATON, FL 33431 ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC

350 BURBANK RD  
OLDSMAR, FL  
(813) 855-2627

3 IN MODULAR GLASS  
GLASS ROOM WITH MONOSLOPE ROOF  
PERFORMANCE EVALUATION

REMARKS	DATE	DRWN	CHKD
ORIGINAL PROJECT 00-29344	5/29/20	TT	FLB
2021 FORMATTING UPDATE 00-29344	11/03/21	OCB	FLB
2023 FBC (23-69327)	01/05/23	CLV	OCB

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.


COPYRIGHT ENGINEERING EXPRESS®

23-69327


SCALE: NTS UNLESS NOTED

3


1 ROOF PANEL TO WOOD HOST SECTION



4 WALL PANEL TO HOST BASE N.T.S. SECTION




7 CONNECTION AT EAVE & POST N.T.S. SECTION




10 CORNER POST TO TOPCAP N.T.S. ELEVATION




2 ROOF PANEL TO WOOD FRAMED WALL N.T.S. SECTION



5 ROOF TO WALL PANEL AT EAVE N.T.S. SECTION




8 ROOF TO WALL PANEL AT RAKE N.T.S. SECTION




11 CORNER COLUMN N.T.S. DETAIL




3 ROOF PANEL TO CONCRETE / CMU WALL N.T.S. SECTION



6 CONNECTION AT EAVE & POST N.T.S. ELEVATION



9 FAN BEAM IN PANEL ROOF N.T.S. DETAIL



12 ROOF PANEL GUTTER N.T.S. DETAIL



3" SNAP-N-LOCK  
COMPOSITE PANEL  
PER SEPARATE  
ENG

#12 SAE GRADE 5  
SHEET METAL  
SCREWS AT 12" O.C.  
EA SIDE, TYP.

1/4" SAE GR 5 THRUBOLTS  
MAY BE USED IN LIEU OF SEX  
BOLTS IN ALL CASES

WINDOW PER  
MANUFACTURERS  
SPECS

13

### HEAD/SILL PANEL FILL

N.T.S.

DETAIL

(1)- 1/4"Ø ITW TAPCON WITH 1 1/2"Ø  
WASHER PER ANGLE, 2 1/4" EMBED,  
3 3/4" EDGE, 3 3/4" MIN. SPACING TO  
ANY ADJACENT CONCRETE ANCHOR  
OR (4)- 1/4"Ø LAG SCREWS WITH 1"Ø  
WASHER, 2 1/2" THREAD  
PENETRATION, 1" EDGE DISTANCE,  
1" MIN. SPACING TO ANY ADJACENT  
WOOD ANCHOR, TYP.

UTILIZE (3)-#12 SAE  
GRADE 5 SMS THROUGH  
EACH CLIP ANGLE TO  
POST, TYP.

2"x2"x0.063"x2"  
LONG 6063-T6  
ALUMINUM ANGLE,  
(1) EA SIDE OF  
POST ON THE  
INSIDE FACE (2  
CLIPS TOTAL). SEE  
PLAN VIEW A-A FOR  
PLACEMENT  
INFORMATION, TYP.

1/4" Ø SAE GRADE 5 SEX BOLTS WITH  
SAE GRADE WASHER THROUGH TOP  
CAP CHANNEL TO POST, TYP.

15

### TYPICAL CORNER POST TIE-DOWN FOR ALL SYSTEMS

N.T.S.

DETAIL

#### ANCHOR# 1 SCHEDULE A:

WIND TIER	ANCHOR TYPE	DESCRIPTION
up to 20 psf	1	(1)- 1/4"Ø SAE GRADE 5 SEX BOLT WITH 1/4" SAE GRADE WASHER
from 20 psf to 30 psf	1	(1)- 3/8"Ø SAE GRADE 5 SEX BOLT WITH 3/8" SAE GRADE WASHER

1/4" Ø SAE GRADE 5  
SEX BOLTS AT 18"  
O.C. AND 4" FROM  
ENDS, TYP.

3" SNAP-N-LOCK  
COMPOSITE PANEL  
PER SEPARATE ENG

WINDOW PER  
MANUFACTURERS  
SPECS

14

### WIND JAMB AT PANEL FILL

N.T.S.

DETAIL

1/4" Ø SAE GRADE 5 SEX  
BOLTS THROUGH KEYED  
RECEIVER TO PANEL, TYP.

(4)- 5/16"Ø SEX BOLTS THROUGH  
KEYED RECEIVER TO MULLION, TYP.

ANCHOR #1: SEE  
SCHEDULE A

SEE DETAIL 9/3 FOR TYPICAL  
ANCHOR TYPE AND SPACING

SEE SCHEDULE FOR  
ANCHOR INFO AND  
QUANTITIES  
REQUIRED, TYP.

ANCHOR #2: SEE  
SCHEDULE B

16

### TYPICAL POST CONNECTION FOR GLASS WALL SYSTEMS

N.T.S.

DETAIL

SEE SHEET 2  
FOR SEX BOLT  
REQUIREMENTS  
FOR STITCHING

3" SNAP-N-LOCK  
PANEL, TYP. PER  
SEPARATE ENG

SEE DETAIL 9/3 FOR  
TYPICAL ANCHOR TYPE  
AND SPACING

EXISTING 3KSI  
CONCRETE OR WOOD  
(G=0.55 MIN.) HOST  
STRUCTURE BY  
OTHERS, TYP.

#### ANCHOR #2 SCHEDULE B:

WIND TIER	ANCHOR 2 SUBSTRATE	QUANTITY REQUIRED
up to 20 psf	CONNECTION AT CONCRETE	(2)- 3/8"Ø ITW TAPCONS WITH 1 1/2"Ø WASHER, 2 1/2" EMBED, 3" EDGE, 4" SPACING, TYP.
	CONNECTION AT WOOD	(3)- 1/4"Ø LAG SCREWS 1 1/2"Ø WASHER, 2 1/2" THREAD PENETRATION, 1" EDGE, 1" SPACING
from 20 psf to 30 psf	CONNECTION AT CONCRETE	(2)- 3/8"Ø ITW TAPCONS WITH 1 1/2"Ø WASHER, 2 1/2" EMBED, 3" EDGE, 4" SPACING, TYP.
	CONNECTION AT WOOD	(4)- 1/4"Ø LAG SCREWS 1 1/2"Ø WASHER, 2 1/2" THREAD PENETRATION, 1" EDGE, 1" SPACING

COPIES WITHOUT  
ORIGINAL PE SEAL NOT  
VALID FOR PERMIT

SPACE RESERVED FOR  
CERTIFYING ENGINEER'S  
DIGITAL OR PHYSICAL SEAL  
& DATE OF CERTIFICATION

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS  
ITEM HAS BEEN DIGITALLY SIGNED BY THE  
ABOVE-SIGNING ENGINEER ON THE DATE  
ADJACENT TO THE SEAL. PRINTED COPIES OF THIS  
DOCUMENT ARE NOT CONSIDERED SIGNED AND  
SEALED AND THE SIGNATURE MUST BE VERIFIED  
ON ANY ELECTRONIC COPIES.  
VISIT [EALC.IQ/IDS](http://EALC.IQ/IDS) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT  
CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE &  
SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR  
USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
VALID FOR 1 PERMIT ONLY U.N.O.

ENGINEERING  
EXPRESS®

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC

350 BURBANK RD

OLDSMAR, FL

(813) 855-2627

3 IN MODULAR GLASS

GLASS ROOM WITH MONOSLOPE ROOF

PERFORMANCE EVALUATION

REMARKS	DATE	DRWN	CHKD
ORIGINAL PROJECT (00-25344)	5/29/20	TT	FLB
2021 FORMATTING UPDATE (00-26246)	11/03/21	OCB	FLB
2023 FBC (23-69327)	01/05/23	CLV	OCB

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, INC. AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

23-69327

SCALE: NTS UNLESS NOTED

4



TABLE 1

POST HEIGHT TABLES


COLUMN TYPE	MAX ROOF SPAN S (FT)	LIVE LOAD GRAVITY (PSF)	LATERAL WIND LOAD (PSF)	AVERAGE COLUMN SPACING W(FT)				
				3'-0"	4'-0"	5'-0"	6'-0"	7'-0"
				ALLOWABLE POST HEIGHT (FT)				
3" Mod Room (Male+ Female)	12'-0"	20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	8'-9"
			40 PSF	10'-0"	10'-0"	9'-4"	8'-4"	7'-7"
			50 PSF	10'-0"	9'-5"	8'-4"	7'-6"	6'-10"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-2"	8'-3"
			40 PSF	10'-0"	10'-0"	9'-0"	8'-0"	7'-2"
			50 PSF	10'-0"	9'-2"	8'-0"	7'-1"	6'-5"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-6"
			30 PSF	10'-0"	10'-0"	9'-11"	8'-9"	7'-9"
			40 PSF	10'-0"	9'-11"	8'-7"	7'-7"	6'-9"
			50 PSF	10'-0"	8'-10"	7'-8"	6'-9"	6'-0"
		50 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-0"
			30 PSF	10'-0"	10'-0"	9'-6"	8'-3"	7'-3"
			40 PSF	10'-0"	9'-7"	8'-2"	7'-2"	6'-4"
			50 PSF	10'-0"	8'-7"	7'-4"	6'-5"	5'-8"

TABLE 2

COLUMN TYPE	MAX ROOF SPAN S (FT)	LIVE LOAD GRAVITY (PSF)	LATERAL WIND LOAD (PSF)	AVERAGE COLUMN SPACING W(FT)				
				3'-0"	4'-0"	5'-0"	6'-0"	7'-0"
				ALLOWABLE POST HEIGHT (FT)				
3" Thermo Mod Room (Male+ Female)	12'-0"	20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-5"	8'-7"
			40 PSF	10'-0"	10'-0"	9'-2"	8'-3"	7'-7"
			50 PSF	10'-0"	9'-3"	8'-3"	7'-6"	6'-11"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	8'-10"
			40 PSF	10'-0"	10'-0"	9'-3"	8'-5"	7'-9"
			50 PSF	10'-0"	9'-4"	8'-4"	7'-6"	7'-0"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	9'-0"
			40 PSF	10'-0"	10'-0"	9'-3"	8'-5"	7'-9"
			50 PSF	10'-0"	9'-4"	8'-4"	7'-7"	7'-0"
		50 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-9"	9'-0"
			40 PSF	10'-0"	10'-0"	9'-3"	8'-5"	7'-9"
			50 PSF	10'-0"	9'-4"	8'-4"	7'-7"	7'-0"

EAVE BEAM

EAVE BEAM CLEAR SPAN ISOMETRIC DETAIL \*



1

5

EAVE BEAM SPACING

N.T.S.

EXPLODED ISOMETRIC

FOAM PANEL EAVE BEAM NOTES:

6" PANEL DEPTH:  
EAVE BEAM SPAN= 5'-0" UP TO 50PSF  
EAVE BEAM SPAN= 6'-0" UP TO 40PSF  
MAX ALLOWABLE CLEAR ROOF SPAN= 12'-0"

7" OR GREATER PANEL DEPTH:  
EAVE BEAM SPAN= 6'-0" UP TO 60PSF  
AT 16' CLEAR ROOF SPAN

SITE SPECIFIC ENGINEERING FOR ADDITIONAL SPANS  
DEFLECTION LIMIT = L/180.

COPIES WITHOUT ORIGINAL PE SEAL NOT VALID FOR PERMIT

SPACE RESERVED FOR CERTIFYING ENGINEER'S DIGITAL OR PHYSICAL SEAL & DATE OF CERTIFICATION

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS ITEM HAS BEEN DIGITALLY SIGNED BY THE ABOVE-SIGNING ENGINEER ON THE DATE ADJACENT TO THE SEAL. PRINTED COPIES OF THIS DOCUMENT ARE NOT CONSIDERED SIGNED AND SEALED AND THE SIGNATURE MUST BE VERIFIED ON ANY ELECTRONIC COPIES.  
VISIT [EOL.CIO/DS](http://EOL.CIO/DS) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE & SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE. VALID FOR 1 PERMIT ONLY UNLESS OTHERWISE NOTED.



POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC

350 BURBANK RD  
OLDSMAR, FL  
(813) 855-2627

3 IN MODULAR GLASS  
GLASS ROOM WITH MONOSLOPE ROOF  
PERFORMANCE EVALUATION

REMARKS	DATE	DRWN	CHKD
ORIGINAL PROJECT (20-29344)	5/29/20	JT	FLB
2021 FORMATTING UPDATE (20-29344)	11/03/21	OCB	FLB
2023 FBC (23-69327)	01/05/23	CLV	OCB

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS, AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS, ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

23-69327

SCALE: NTS UNLESS NOTED

TABLE 3

COLUMN TYPE	MAX ROOF SPAN S (FT)	LIVE LOAD GRAVITY (PSF)	LATERAL WIND LOAD (PSF)	AVERAGE COLUMN SPACING W(FT)				
				3'-0"	4'-0"	5'-0"	6'-0"	7'-0"
				ALLOWABLE POST HEIGHT (FT)				
3" Mod Room (Female+ Female) w/ 3x3 insert	12'-0"	20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	8'-9"
			40 PSF	10'-0"	10'-0"	9'-4"	8'-4"	7'-7"
			50 PSF	10'-0"	9'-5"	8'-4"	7'-6"	6'-10"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-2"	8'-3"
			40 PSF	10'-0"	10'-0"	9'-0"	8'-0"	7'-2"
			50 PSF	10'-0"	9'-2"	8'-0"	7'-1"	6'-5"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-6"
			30 PSF	10'-0"	10'-0"	9'-11"	8'-9"	7'-9"
			40 PSF	10'-0"	9'-11"	8'-7"	7'-7"	6'-9"
			50 PSF	10'-0"	8'-10"	7'-8"	6'-9"	6'-0"
		50 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	9'-0"
			30 PSF	10'-0"	10'-0"	9'-6"	8'-3"	7'-3"
			40 PSF	10'-0"	9'-7"	8'-2"	7'-2"	6'-4"
			50 PSF	10'-0"	8'-7"	7'-4"	6'-5"	5'-8"

POST HEIGHT:

POST SPACING  
ISOMETRIC DETAIL\*




TABLE 4

COLUMN TYPE	MAX ROOF SPAN S (FT)	LIVE LOAD GRAVITY (PSF)	LATERAL WIND LOAD (PSF)	AVERAGE COLUMN SPACING W(FT)				
				3'-0"	4'-0"	5'-0"	6'-0"	7'-0"
				ALLOWABLE POST HEIGHT (FT)				
3" Thermo Mod Room (Female+ Female) w/ 3x3 insert	12'-0"	20 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-5"	8'-7"
			40 PSF	10'-0"	10'-0"	9'-2"	8'-3"	7'-7"
			50 PSF	10'-0"	9'-3"	8'-3"	7'-6"	6'-11"
		30 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	8'-10"
			40 PSF	10'-0"	10'-0"	9'-3"	8'-5"	7'-9"
			50 PSF	10'-0"	9'-4"	8'-4"	7'-6"	7'-0"
		40 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-8"	9'-0"
			40 PSF	10'-0"	10'-0"	9'-3"	8'-5"	7'-9"
			50 PSF	10'-0"	9'-4"	8'-4"	7'-7"	7'-0"
		50 PSF	20 PSF	10'-0"	10'-0"	10'-0"	10'-0"	10'-0"
			30 PSF	10'-0"	10'-0"	10'-0"	9'-9"	9'-0"
			40 PSF	10'-0"	10'-0"	9'-3"	8'-5"	7'-9"
			50 PSF	10'-0"	9'-4"	8'-4"	7'-7"	7'-0"

TABLE 5

COLUMN TYPE	MAX ROOF SPAN S (FT)	LIVE LOAD GRAVITY (PSF)	LATERAL WIND LOAD (PSF)	AVERAGE COLUMN SPACING W(FT)				
				3'-0"	4'-0"	5'-0"	6'-0"	7'-0"
				ALLOWABLE POST HEIGHT (FT)				
3" Thermo Mod Room (Male+ Male W/ I Beam Insert)	12'-0"	20 PSF	20 PSF	9'-7"	8'-1"	7'-0"	6'-2"	5'-6"
			30 PSF	7'-10"	6'-7"	5'-8"	5'-0"	4'-6"
			40 PSF	6'-10"	5'-8"	5'-0"	4'-4"	-
			50 PSF	6'-1"	5'-1"	4'-5"	-	-
		30 PSF	20 PSF	9'-2"	7'-6"	6'-4"	5'-6"	4'-9"
			30 PSF	7'-6"	6'-2"	5'-2"	4'-6"	-
			40 PSF	6'-6"	5'-4"	4'-6"	-	-
			50 PSF	5'-9"	4'-9"	4'-0"	-	-
		40 PSF	20 PSF	8'-8"	7'-0"	5'-9"	4'-10"	4'-0"
			30 PSF	7'-1"	5'-8"	4'-8"	-	-
			40 PSF	6'-2"	5'-0"	4'-1"	-	-
			50 PSF	5'-6"	4'-5"	-	-	-
		50 PSF	20 PSF	8'-2"	6'-5"	5'-2"	4'-2"	-
			30 PSF	6'-8"	5'-3"	4'-2"	-	-
			40 PSF	5'-10"	4'-6"	-	-	-
			50 PSF	5'-2"	4'-1"	-	-	-

TABLE NOTES:

- DEFLECTION LIMIT = L/180 USED IN TABLE RESULTS.
- VALUES BELOW ALLOWABLE CEILING HEIGHT INTENDED TO BE BUILT ON KNEEWALLS OR OTHER SUPPORTING STRUCTURES (CERTIFIED BY OTHERS).
- RESULTS FOR THERMALLY BROKEN POSTS SHALL BE REDUCED BY 10% TO ACCOUNT FOR THERMAL BREAK STRENGTH LOSS.

COPIES WITHOUT  
ORIGINAL PE SEAL NOT  
VALID FOR PERMIT

SPACE RESERVED FOR  
CERTIFYING ENGINEER'S  
DIGITAL OR PHYSICAL SEAL  
& DATE OF CERTIFICATION

DIGITAL SEAL NOTICE:  
IF THIS DOCUMENT IS DIGITALLY SIGNED, THIS  
ITEM HAS BEEN DIGITALLY SIGNED BY THE  
ABOVE-SIGNING ENGINEER ON THE DATE  
ADJACENT TO THE SEAL. PRINTED COPIES OF THIS  
DOCUMENT ARE NOT CONSIDERED SIGNED AND  
SEALED AND THE SIGNATURE MUST BE VERIFIED  
ON ANY ELECTRONIC COPIES.  
VISIT [EALC.IQ/IDS](http://EALC.IQ/IDS) FOR MORE INFORMATION.  
PRINTED DOCUMENT NOTICE:  
IF THIS DOCUMENT IS PRINTED & DOES NOT  
CONTAIN AN ENGINEER'S ORIGINAL SIGNATURE &  
SEAL, THIS DOCUMENT IS VOID & NOT VALID FOR  
USE. PHOTOCOPIES ARE NOT PERMITTED FOR USE.  
VALID FOR 1 PERMIT ONLY U.N.O.

ENGINEERING  
EXPRESS®

POSTAL ADDRESS:  
2234 NORTH FEDERAL HWY #7664  
BOCA RATON, FL 33431  
ENGINEERINGEXPRESS.COM

STRUCTALL BUILDING SYSTEMS, INC

350 BURBANK RD  
OLDSMAR, FL  
(813) 855-2627

3 IN MODULAR GLASS  
GLASS ROOM WITH MONOSLOPE ROOF  
PERFORMANCE EVALUATION

REMARKS	DRWN	CHKD	DATE
ORIGINAL PROJECT (00-2634)	TT	FLB	5/29/20
2021 EXPIRATION DATE (00-2634)	CCB	FLB	11/03/21
2023 FBC (23-69327)	CLV	OCB	01/05/23

THIS DOCUMENT IS THE PROPERTY OF ENGINEERING EXPRESS,  
AND SHALL NOT BE REPRODUCED IN WHOLE OR PART WITHOUT  
WRITTEN CONSENT OF ENGINEERING EXPRESS. ALTERATIONS,  
ADDITIONS, OR OTHER MARKINGS TO THIS DOCUMENT ARE NOT  
PERMITTED AND INVALIDATE OUR CERTIFICATION.

COPYRIGHT ENGINEERING EXPRESS®

23-69327

SCALE: NTS UNLESS NOTED

6